



## PT INDUSTRIAL CONTROL CABINET

### PT series Industrial Control Cabinet Specification

- 1、 **Frame(PATENT) is made of double profile and connected BY 3 tee, could be welding and un welding, static loading capacity is 1500kgs.**
- 2、 There are round holes distributed on the rectangle frame by each 25MM as unit, this is not only to enhance the strength for the cabinet, but also to install or fix the cables or other electronic component.
- 3、 The unit distance for installation bar is 25mm, depth could be adjusted by units(minimum 25mm)
- 4、 There are round and square holes distributed at the double profile for at a even 25mm distance on four areas.
- 5、 Top cover, side door, back pane and bottom are all fixed by fastens, easy for fixing and unfixing
- 6、 P Degree : IP55
- 7、 Three parts bottom cover which each parts can change flexible
- 8、 Easy installation for plinth (Optional Part)
- 9、 We could make customized request like change for size or holing

#### **SURFACE FINISH:**

DEGREASING、PICKLING、PHOSPHATING、POWER COATED; BRUSHED STAINLESS STEEL

#### **MATERIAL:**

COLD ROLLED STEEL(SPCC) OR STAINLESS STEEL(SUS304).

THE THICKNESS OF THE DOOR IS 2.0MM, THE BODY OF THE CABINET IS 1.5MM, THE INSTALLING PLATE IS 2.5MM

**COLOR:** MAIN BODY: RAL7035      INSTALLING PLATE: ORIGINAL COLOR OF GALVANIZED PLATE OR RAL2000

- PACKAGE WAY:** 1、 ASSEMBLED PACKAGE  
2、 FLAT PACKAGE

#### ORDER CODE

ITEM NO.	WIDTH*DEPTH*HEIGHT(MM)	ITEM NO.	WIDTH*DEPTH*HEIGHT(MM)
PT4684	600*400*1800	PT4884	800*400*1800
PT4084	100*400*1800	PT4284	1200*400*1800
PT4685	600*500*1800	PT4885	800*500*1800
PT4085	1000*500*1800	PT4285	1200*500*1800
PT4686	600*600*1800	PT4886	800*600*1800
PT4086	1000*600*1800	PT4286	1200*600*1800
PT4688	600*800*1800	PT4888	800*800*1800
PT4088	1000*800*1800	PT4288	1200*800*1800
PT4604	600*400*2000	PT4804	800*400*2000
PT4004	1000*400*2000	PT4204	1200*400*2000
PT4605	600*500*2000	PT48050	800*500*2000
PT4005	1000*500*200	PT4205	1200*500*2000

PT4606	600*600*2000	PT4806	800*600*2000
PT4006	1000*600*2000	PT4206	1200*600*2000
PT4608	600*800*2000	PT4808	800*800*2000
PT4008	1000*800*2000	PT4208	1200*800*2000
PT4624	600*400*2200	PT4824	800*400*2200
PT4024	1000*400*2200	PT4224	1200*400*2200
PT4625	600*500*2200	PT4825	800*500*2200
PT4025	1000*500*2200	PT4225	1200*500*2200
PT4626	600*600*2200	PT4826	800*600*2200
PT4026	1000*600*2200	PT4226	1200*600*2200
PT4628	600*800*2200	PT4828	800*800*2200
PT4028	1000*800*2200	PT4228	1200*800*2200

PACKAGE WAY: 1、ASSEMBLED PACKAGE

2、FLAT PACKAGE

